



Home \ Product Categories \ Circulation Fans \ Fixed Mount Circulation Fans \ VK12

12" Versa-Kool Circulation Fan VK12

Product Description

Reduce heat stress and improve air quality with Schaefer's uniquely designed circulation fans. Unrivaled in the market, these fans are engineered to produce greater air movement and superior cooling no matter the application. You don't hear them. You don't see them. You only feel them!

Also known as Horizontal Air Flow (HAF) fans, these fans move air in a coherent horizontal pattern creating a gentle 'racetrack' air flow pattern needed in greenhouses to maximize heat distribution and humidity control by mixing the air, from ceiling to floor.

Features

- Deep guard design for unmatched performance, low noise levels and safety without sacrificing airflow
- Matched high quality motors and blades for maximum efficiency
- Powder coated steel guards for increased durability and corrosion resistance
- Hot dipped galvanized guards on VK12-GA and VK20-GA models for even greater rust protection
- Powder coated steel mounting bracket and power cord included
- Wide variety of mounting options available for flexible and easy installation
- Variable speed controls available
- Misting kits available for even greater cooling
- Two year warranty
- Made in the USA



SPECIFICATIONS

Air Velocity (@ 10')	TBD
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	1470
Drive	Direct
Mount Included	VS12FMT
Phase	1
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	14
Cord	Included - Not Wired
Diameter (inches)	12
Frequency (hz)	60
Guard Color	White

Mount Type Included	Ceiling
Nameplate Amps	1.3/65
Number Of Wings	3
Bess Lab Performance Test #	12370
Power (hp)	1/10
Product Net Weight (lbs)	18
Switch	Not included
Voltage	115/230
Maximum Rpm	1725
Air Velocity (@ 5 Times Diameter)	680
Blade Material	Aluminum
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White
Product Shipping Dimensions (in)	15 x 15 x 17

Speed Control Compatible?	Yes
Able To Ship Small Parcel	Yes
Cfm Range (free Air)	1001 - 2500
Cord Length (feet)	5
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Country Of Origin	US
Guard Spacing (inches)	1/2 - 1 UL507
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm/watt (@0.05")	TBD